


DURiTE ECO

RGB3S 0.72W



FEATURES

- Full color with natural color projection
- Ensures excellent transmittance and uniform lighting
- Specially designed durable cover that withstands harsh environment and protects the LED
- Easy installation with double sided 3M tape
- IP68 Waterproof and approved by UL, CE, RoHS
- Compact design with vivid and eliminates hot spots
- Long life time 50,000 hours

DESCRIPTION

DURiTE ECO Series is Specialized for Channel Letter Signs.

The LED is powered by Reliable Korean LED that makes high performance and durability as Tier 1 LED.


Starux's most cost-efficient model and easy installation with double sided 3M tape.

The ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

Model	ECO RGB3S 0.72W			Module Spacing	2 pcs/ft
Colors	RGB Full Color			Demension	2.8" x 0.6" x 0.4"
Wavelength(nm)	R:620~625	G:520~525	B:460~465	Weight	10g
Power	0.72W			Max in series	35 Mods
Input Voltage	12V DC			Operating Temp.	-4°F ~ 122°F / -20°C ~ 50°C
Forward Current	60 mA			Life Time	50,000
Beam Angle	150°			IP Rating	IP68 Waterproof

DIMENSION



COVERAGE CHART

Depth	3"	4"	5"	6"~8"
Max Stroke Single Row	8"	10"	12"	14"
Max Stroke Multi Rows	6"	10"	12"	14"
Mods per ft	2 pcs per ft			

Parameters can be adjusted according to the desired brightness.